WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: C12M 1/00, 3/00, 3/04, C08J 9/26

A1

(11) International Publication Number:

WO 97/08291

(43) International Publication Date:

6 March 1997 (06.03.97)

(21) International Application Number: PCT/GB96/02070

(22) International Filing Date:

23 August 1996 (23.08.96)

(30) Priority Data:

9517717.6 9526032.9

31 August 1995 (31.08.95) GB

20 December 1995 (20.12.95) GB

(71) Applicant (for all designated States except US): ASHBY SCI-ENTIFIC LTD. [GB/GB]; Unit 11, Atlas Court, Coalville, Leics. LE67 3FL (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): FULLER, Jess, Paul [GB/GB]; Flat 7, 35 Nottingham Road, Ashby-de-la-Zouch, Leics. LE65 1DL (GB).


(74) Agents: JUMP, Timothy, John, Simon et al.; Venner, Shipley & Co., 20 Little Britain, London EC1A 7DH (GB).

(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: APPARATUS AND METHODS FOR CULTURING BIOLOGICAL MATERIAL



(57) Abstract

A method of providing a substrate with a textured surface comprising the steps of forming a mobile surface studded with a granular material on the substrate, setting the mobile surface and removing the granular material to leave a textured surface on said substrate, and apparatus for use in culturing micro-biological material comprising a substrate produced by such a method.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM AT AU BB BE BF BG BJ CA CF CG CH CI CM CN CS CZ DE DK EE ES FI FR GA	Armenia Austria Austria Australia Barbados Belgium Burkina Faso Bulgaria Benin Brazil Belarus Canada Central African Republic Congo Switzerland Côte d'Ivoire Cameroon China Czechoslovakia Czech Republic Germany Denmark Estonia Spain Finland France Gabon	GB GE GN GR HU IE IT JP KE KG KP KR KZ LI LK LR LT LU MC MD MG ML MN MR	United Kingdom Georgia Guinea Greece Hungary Ireland Italy Japan Kenya Kyrgystan Democratic People's Republic of Korea Republic of Korea Kazakhstan Liechtenstein Sri Lanka Liberia Lithuania Luxembourg Latvia Monaco Republic of Moldova Madagascar Mali Mongolia Mauritania	MW MX NE NL NO NZ PL PT RO SE SG SI SK SN SZ TD TG TG TJ TT UA UG US UZ VN	Malawi Mexico Niger Netherlands Norway New Zealand Poland Portugal Romania Russian Federation Sudan Sweden Singapore Slovenia Slovakia Senegal Swaziland Chad Togo Tajikistan Trinidad and Tobago Ukraine Uganda United States of America Uzbekistan Viet Nam
---	---	--	--	--	---

- 1 -

APPARATUS AND METHODS FOR CULTURING BIOLOGICAL MATERIAL

DESCRIPTION

5

The present invention relates to vessels having textured surfaces for growing animal cells, plant cells, microorganisms and the like ('bio-substances') and to methods for their production.

10

Many bio-substances can be propagated in vitro in containers such as so-called 'roller bottles', that is, cylindrical vessels, usually of glass or polystyrene, which are partially filled with a liquid medium comprising the bio-substances. The bottles are arranged to be rotated slowly about their longitudinal axes, promoting aeration, while the liquid medium provides nutrients to the bio-substances as they grow on the inner surfaces of the container.

20

Limitations in the efficiency of conventional procedures have hitherto been due to the relatively small surface area provided by the smooth interior of the container, as well as the fact that such surfaces do not provide optimum characteristics for the growth processes. It is an object of the present invention to eliminate or minimise these disadvantages.

- 2 -

Accordingly, in a first aspect of the invention, there is provided apparatus for use in a method of culturing micro-biological material, wherein said apparatus defines a rough or uneven growth surface arranged for contact with micro-biological material being cultured. An advantage of the inventive apparatus is that its use can allow cultured material to be grown at enhanced rates.

Preferably, the growth surface is rendered rough or uneven by surface features having a depth of 1mm or less and, preferably, a depth of 0.1-0.5mm. In preferred embodiments, the growth surface is pitted, or pockmarked with a plurality of craters or crater like depressions, preferably to depths of 1mm or less and more preferably to depths of 0.1-0.5 mm. Preferably, the craters or crater like depressions measure less than 5, preferably less than 2, and more preferably less than 1mm across. Most preferably, the crater or crater like depressions measure less than 0.5mm across.

20

In further embodiments, the growth surface is microcupellated and it can be formed from an organic polymer. The polymer can be coated onto a supporting substrate and, preferably, is a silicone rubber. In an embodiment, the growth surface forms an inner surface of a container for retaining biological material being cultured.

In a second aspect, the invention provides a method of

material to be grown at an enhanced rate.

culturing a micro-biological material, comprising culturing said material using apparatus defining a growth surface, wherein said material is in contact with the growth surface and the growth surface is uneven or rough.

5 Advantageously the inventive method allows biological

- 3 -

Preferably, the apparatus employed in the second aspect of the invention is in accordance with its first aspect.

10

In a third aspect, the invention provides a method of providing a substrate with a textured surface comprising the steps of forming a mobile surface studded with a granular material on the substrate, setting the mobile surface and removing the granular material to leave a textured surface on said substrate.

In a fourth aspect of the invention, there is provided an article having a textured surface that can be obtained by a method according to the invention in its third aspect.

Preferably, the article is a tissue or cell culture vessel, such as a roller-bottle.

In all aspects of the invention the biological material preferably comprises tissue, cells or like matter, including viral particles or virions.

In the invention according to its fourth aspect, the

WO 97/08291 PCT/GB96/02070 4 -

mobile surface is preferably tacky prior to the setting step, so as to promote adherence of the granular In a preferred embodiment, a (preferably material. solvent-less) silicone paint, designed for polymerisation 5 to form silicone rubber, is applied to the interior surface of a glass or polystyrene roller bottle. While the coating is still in liquid form, common salt particles are injected into the container, for example, under pressure, to adhere to the prepared silicone coating, with any excess salt being removed again from the container. The coating is then allowed to polymerise into a solid layer at ambient or elevated temperature, depending on the type of silicone used. When hardened, the salt particles adhering to the coating are removed by 15 dissolution in water, to leave a surface-porous layer exhibiting a cratered or micro-cupellated structure, as well as the special affinity for bio-substances of silicone rubber. The container so prepared is found to result in a greatly increased yield when used for growth processes in the manner described.

To promote adhesion of the silicone rubber layer within or polystyrene container, a conventional adhesive, preferably a mineral spirit based primer, can be first applied to the surface prior to deposition of the silicone layer.

In embodiments of the invention, it is a pre-requisite

that the growth surface should be non-toxic and inert in respect of bio-substances and liquid media. The method of creating such surfaces should not involve any materials, which if remaining on the surface as impurities, could have a deleterious effect on the growth process.

In the above described method, various types of particles can be used in place of common salt, such as, for example, sugar, saltpetre and the like; however, common salt is preferred as being non-toxic and inert in respect of normal media and bio-substances, as well as being soluble in water for subsequent removal. Solubility of the particles in a non-toxic solvent is an important factor in their choice.

15

Attempts have been made to use 'open-porous' silicone rubbers, such as the material 'Immobasil' ('Immobasil' is a registered trade mark); however, the results obtained were not as satisfactory as those achievable using the various aspects of the present invention. The open-porous structure (that is, the presence of inter-connected pores within the body of the silicone rubber) in such known materials leads to difficulties in the subsequent harvesting of the biosubstances from the interstices of the coating on completion of a growth cycle.

In an embodiment of the invention, surface pitting or cratering, for example, micro-cupels, can be produced in

- 6 -

the inner surfaces of glass or polystyrene containers per For this purpose, salt or other suitable particles se. injected, for example, pneumatically, into the container while the latter is at elevated temperature, 5 either during its manufacture or on subsequent heating. Upon cooling, the particles are then removed as described above, leaving the interior surface of the glass or polystyrene container with a textured, cratered or microcupellated structure, again resulting in enhanced efficiency of the process. In the case of polystyrene containers, prior to use, the standard procedure of plasma treatment of the inner surface can be applied to impart a negative electrical charge to the surface, as required for the growth process. Other types of particle can be used apart from salt, the latter however, being again preferred for the reasons enumerated.

It is evident that other methods lying within the ambit of the invention may also be used to derive surface porous, cratered or micro-cupellated textured surfaces of the nature described for growing of bio-substances. The invention can equally be applied to all suitable containers, such as, for example, flasks, tubes, trays, roller bottles, plastic bags and the like.

25

15

In applications where very large area growth surfaces are required, it is conventional to utilise containers which comprise flat plates, for example, of polystyrene, wetted

by the liquid medium, and upon which the bio-substances are made to grow. Such plates can also be provided with coatings of silicone rubber having a cratered or micro-cupellated, porous, surface structure according to the invention, in the manner described above, to result in substantially enhanced productivity.

Thus, roller bottles and other containers according to the invention can have a specially textured, cratered or micro-cupellated growth surface, usually an inner surface, suitable for use in the growth of bio-substances as aforesaid. By their nature, these surfaces are more conducive to the adhesion and growth of bio-substances, with resulting improved process efficiency. It is considered that the larger surface areas provided by such growth surfaces is a factor in their enhanced performance.

In order that the invention may be better understood, an example thereof will now be described by way of illustration only and with reference to the accompanying drawings, wherein:

Figure 1 is a schematic front perspective view of a 25 conventional roller bottle;

Figure 2 is a schematic side cross-sectional view of the roller bottle of Figure 1 along the line AA' after

partial treatment by the inventive method;

Figure 3 is a schematic side cross-sectional view of the roller bottle of Figure 2 after treatment by the inventive method has been completed; and

Figure 4 is a schematic scrap view from a point on the axis of the roller bottle showing a portion of the growth surface after treatment by the inventive method has been completed.

With reference to Figures 1 to 4, a polystyrene roller bottle 1 is provided with a cratered or micro-cupellated surface according to the inventive method as follows. To the interior surface of bottle 1, a coating 2 of silicone 15 rubber primer SS 4155 (General Electric Co., Connecticut, U.S.A.) is applied by brushing or other means and allowed to dry at 70°C for 15 minutes. A coating 3 of silicone rubber paint RTV 118 (General Electric Co., Connecticut, U.S.A.), approximately 0.05 to 0.2mm in 20 thickness, is applied to primer coating 2 and left to stand for 1 minute. A substantial quantity of common 4 is then introduced into bottle 1 until approximately 1/3 full and the latter shaken, so that salt 4 adheres to all of the paint coating 3. The excess 25 salt 4 is removed and coating 3 allowed to cure at 70°C for 30 mins. Bottle 1 is then filled with boiling water and allowed to stand for 10 minutes before the water is

removed. This last step is repeated once before bottle 1 is rinsed with isopropyl alcohol and left to dry at 70°C for 30 mins. The resultant roller bottle 1 has a textured interior surface 5 provided by craters or microcupels 6 inset in silicone rubber layer 4.

The roller bottle 1 can then be inoculated with a biological material, for example cells taken from a commercially available cell line such as Madin Darby 10 Canine Kidney, suspended in an appropriate commercially available nutrient medium, such as Glucose Minimum foetal calf serum, Essential Medium containing 5% selected for its suitability for growing the chosen The roller bottle can then be placed upon cells. 15 conventional equipment designed to gently roll the bottle under conditions conducive to growing cells from the For example, a common culturing selected line. temperature is 37°C. After an appropriate culturing period, the growing cells can be harvested from the 20 roller bottle using conventional techniques, such as trypsination or mechanical scraping.

<u>CLAIMS</u>

- Apparatus for use in a method of culturing microbiological material, wherein said apparatus defines a rough or uneven growth surface arranged for contact with micro-biological material being cultured.
- 2. Apparatus as claimed in claim 1, wherein the growth surface is rendered rough or uneven by surface features having a depth of 1mm or less and, preferably, a depth of 0.1-0.5mm.
- 3. Apparatus as claimed in claim 1, wherein said 15 growth surface is pitted.
 - 4. Apparatus as claimed in any of claims 1-3, wherein a plurality of craters or crater like depressions are defined in the growth surface.

20

5. Apparatus as claimed in claim 3 or claim 4, wherein the growth surface is pitted or cratered to depths of 1mm or less and, preferably, to depths of 0.1-0.5mm.

25

6. Apparatus as claimed in claim 5, wherein the craters or crater like depressions measure less than 2mm, preferably less than 1mm, and more preferably less

PCT/GB96/02070

than 0.5mm across.

7. Apparatus as claimed in any of the preceding claims, wherein the growth surface is micro-cupellated.

5

- 8. Apparatus as claimed in any of the preceding claims, wherein the growth surface comprises an organic polymer.
- 10 9. Apparatus as claimed in claim 8, wherein the polymer is coated onto a supporting substrate.
 - 10. Apparatus as claimed in claim 8 or claim 9, wherein said polymer is a silicone rubber.

15

11. Apparatus as claimed in any of the preceding claims, wherein the growth surface forms an inner surface of a container for retaining biological material being cultured.

- 12. A method of culturing a micro-biological material, comprising culturing said material using apparatus defining a growth surface, wherein said material is in contact with the growth surface and the growth surface is uneven or rough.
 - 13. A method as claimed in claim 12, wherein the apparatus comprises apparatus as claimed in any one of

- 12 -

claims 1-11.

- 14. A method of providing a substrate with a textured surface comprising the steps of forming a mobile

 5 surface studded with a granular material on the substrate, setting the mobile surface and removing the granular material to leave a textured surface on said substrate.
- 10 15. A method as claimed in claim 14, wherein the mobile surface is tacky prior to setting.
- 16. A method as claimed in claims 14 or 15, wherein the mobile surface is formed by softening the substrate and studding the softened substrate with a granular material.
 - 17. A method as claimed in claims 14 or 15, wherein the mobile surface is formed by coating the substrate

 0 with a layer of a surface-forming material and studding said layer with a granular material.
- 18. A method as claimed in claims 14 or 15, wherein the mobile surface is formed by coating the substrate with a layer of a surface-forming material in admixture with a granular material.
 - 19. A method as claimed in claims 17 or 18, wherein

- 13 -


the surface-forming material is a silicone rubberforming material.

- 20. A method as claimed in claims 17, 18 or 19,
 5 wherein the substrate is treated with an adhesive prior to coating with the layer of surface-forming material.
- 21. A method as claimed in any one of claims 14-20 the preceding claims, wherein the substrate is a glass or an organic polymer.
 - 22. A method as claimed in any one of claims 14-21, wherein the granular material is soluble and is removed by dissolution.


- 23. A method as claimed in claim 22, wherein the granular material is sucrose, salt or potassium nitrate.
- 20 24. A method as claimed in any one of claims 14-23, wherein the textured surface is cratered or microcupellated.
- 25. An article having a textured surface obtained or 25 obtainable by a method as claimed in any one of claims 14-24.
 - 26. Apparatus as claimed in any of claims 1-11

comprising an article as claimed in claim 25.

27. A method as claimed in claim 12, wherein the apparatus comprises apparatus as claimed in claim 26.



2/2



A. CLASSIFICATION OF SUBJECT MATTER IPC 6 C12M1/00 C12M3/00

C12M3/04

C08J9/26

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols) IPC 6 C12M C08J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 41 32 379 A (KERNFORSCHUNGSZ KARLSRUHE) 8 April 1993 see claims; figures 1,2	1-8, 11-13, 26,27
P,X	WO 95 24464 A (BAXTER INT ET AL) 14 September 1995 see claims 1-5	1,2,8, 11-13
X	GB 2 262 538 A (CORNING INC) 23 June 1993 see claims 1-5; figures	1,2,8, 11-13
X	FR 2 522 014 A (PASTEUR INSTITUT) 26 August 1983	1-13,26, 27
Y	see claims 1,7-11,13-15; figures 1,2,5; example 2	9,10
	-/	

X Further documents are listed in the continuation of box C.	Patent family members are listed in annex.
* Special categories of cited documents: 'A' document defining the general state of the art which is not considered to be of particular relevance 'E' earlier document but published on or after the international filing date 'L' document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) 'O' document referring to an oral disclosure, use, exhibition or other means 'P' document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention. "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone. "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family
Date of the actual completion of the international search	Date of mailing of the international search report
22 November 1996	2 9. 11. 96
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentiaan 2	Authorized officer
NL - 2280 HV Rijswijk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+ 31-70) 340-3016	Coucke, A

Form PCT/ISA/210 (second sheet) (July 1992)

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Dalamana an atair St
	what and and and appropriate, of the relevant passages	Relevant to claim No.
X	US 4 912 058 A (MUSSI EDWARD F ET AL) 27 March 1990	1-8, 11-13, 26,27
Y	see claim 1; examples see column 5, line 37 - line 43; claims 1-10; figures	9,10
X	GB 1 092 634 A (IMPERIAL CHEMICAL INDUSTRIES LTD) 29 November 1967	1-6,8, 12,13, 26,27
	see claims	20,2,
X	US 4 320 198 A (MYNATT ROY L) 16 March 1982	1-3,5, 12,13, 26,27
	see abstract; claims 1,2; figures	
(US 4 376 826 A (MYNATT ROY L) 15 March 1983	1-3,5, 12,13, 26,27
	see abstract; claims; figures	20,27
P,X	DE 44 10 718 A (BODE CHEMIE GMBH & CO) 12 October 1995 see page 1, line 30 - line 33; claims 1-6	1,11-13, 26,27
(DATABASE WPI Section Ch, Week 7637 Derwent Publications Ltd., London, GB; Class A85, AN 76-69743X XP002019186 & JP 51 087 578 A (MATSUSHITA ELEC WOR), 1 August 1976 see abstract	14,18, 21,22, 24,25
	US 4 859 712 A (COX JAMES E) 22 August 1989 see the whole document	18,19
	DATABASE WPI Section Ch, Week 8911 Derwent Publications Ltd., London, GB; Class A35, AN 89-079526 XP002019187 & JP 01 022 934 A (POLYPLASTICS KK), 25 January 1989	14-18, 21-25
	see abstract	19
	US 4 284 275 A (FLETCHER HERBERT E) 18 August 1981	14-17, 20-25
İ	see abstract; claims	18,19

6

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

form on patent family members

In al Application No
PCT/GB 96/02070

Patent document cited in search report	Publication date	Patent famil member(s)	у	Publication date
DE-A-4132379	08-04-93	EP-A- 0 JP-B- 2	307258 605527 511247 507076	15-04-93 13-07-94 26-06-96 11-08-94
WO-A-9524464	14-09-95	CA-A- 2 EP-A- 0	060195 162465 698085 512480	25-09-95 14-09-95 28-02-96 30-04-96
GB-A-2262538	23-06-93	AU-B- AU-A- 2 CA-A- 2 EP-A- 0	272084 662371 994392 079569 552412 038734	21-12-93 31-08-95 24-06-93 19-06-93 28-07-93 15-02-94
FR-A-2522014	26-08-83	NONE		
US-A-4912058	27-03-90	EP-A- 0 IE-B- JP-A- 2	006624 394713 63833 303479 028721	24-03-94 31-10-90 14-06-95 17-12-90 05-04-95
GB-A-1092634		NONE		
US-A-4320198	16-03-82	NONE		
US-A-4376826	15-03-83	NONE		
DE-A-4410718	12-10-95	NONE		
US-A-4859712	22-08-89	CH-A- DE-A- 3 FR-A- 2 GB-A,B 2 IE-B-	000448 678946 934149 637537 225016 63980 237813	12-04-90 29-11-91 19-04-90 13-04-90 23-05-90 28-06-95 18-06-93

INTER TIONAL SEARCH REPORT

pcT/GB 96/02070

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
US-A-4859712		JP-A- NL-A- SE-A-	2251544 8902531 8903340	09-10-90 01-05-90 13-04-90
US-A-4284275	18-08-81	NONE		

Form PCT/ISA/210 (patent family annex) (July 1992)